

43	99.01	182.80	105.11
44	115.31	220.77	118.37
45	134.87	267.75	133.87
46	158.50	326.20	152.10
47	187.21	399.36	173.64
48	222.30	491.56	199.26
49	265.50	608.54	229.92
50	319.06	758.09	266.88

Coefficients de portance pour le
calcul des fondations superficielles

ϕ	Nq	N γ	Nc
0	1.00	0.00	5.14
1	1.09	0.00	5.38
2	1.20	0.01	5.63
3	1.31	0.03	5.90
4	1.43	0.06	6.19
5	1.57	0.10	6.49
6	1.72	0.15	6.81
7	1.88	0.22	7.16
8	2.06	0.30	7.53
9	2.25	0.40	7.92
10	2.47	0.52	8.34
11	2.71	0.66	8.80
12	2.97	0.84	9.28
13	3.26	1.05	9.81
14	3.59	1.29	10.37
15	3.94	1.58	10.98
16	4.34	1.91	11.63
17	4.77	2.31	12.34
18	5.26	2.77	13.10
19	5.80	3.30	13.93
20	6.40	3.93	14.83
21	7.07	4.66	15.81
22	7.82	5.51	16.88
23	8.66	6.50	18.05
24	9.60	7.66	19.32
25	10.66	9.01	20.72
26	11.85	10.59	22.25
27	13.20	12.43	23.94
28	14.72	14.59	25.80
29	16.44	17.12	27.86
30	18.40	20.09	30.14
31	20.63	23.59	32.67
32	23.18	27.72	35.49
33	26.09	32.59	38.64
34	29.44	38.37	42.16
35	33.30	45.23	46.12
36	37.75	53.40	50.59
37	42.92	63.18	55.63
38	48.93	74.90	61.35
39	55.96	89.01	67.87
40	64.20	106.05	75.31
41	73.90	126.74	83.86
42	85.37	151.94	93.71